

# Coverage Chart

## Requirements

**Pounds (KG) of Grout required per 100 square feet (9.2M<sup>2</sup>)**

TILE SIZE	JOINT WIDTH	SUPREME & MP NONSANDED
4-1/4" x 4-1/4" x 5/16" (107.9 x 107.9 x 7.9 mm)	1/16" (1.6 mm)	7 (3.2)
1" x 1" x 1/4" (107.9 x 107.9 x 7.9 mm)	1/16" (1.6 mm)	21 (9.5)
1" x 2" x 1/4" (25.4 x 50.8 x 6.4 mm)	1/16" (1.6 mm)	16 (7.3)
2" x 2" x 1/4" (50.8 x 50.8 x 6.4 mm)	1/16" (1.6 mm)	11 (5.0)
TILE SIZE	JOINT WIDTH	MP SANDED & AR GROUT
4" x 4" x 1/2" (101.6 x 101.6 x 12.7 mm)	1/4" (6.4 mm)	48 (21.8)
	3/8" (9.5 mm)	70 (31.8)
	1/2" (12.7 mm)	89 (40.4)
4" x 8" x 1/2" (101.6 x 203.2 x 12.7 mm)	1/4" (6.4 mm)	37 (16.8)
	3/8" (9.5 mm)	54 (24.5)
	1/2" (12.7 mm)	70 (31.8)
6" x 6" x 1/2" (152.4 x 152.4 x 12.7 mm)	1/4" (6.4 mm)	34 (15.4)
	3/8" (9.5 mm)	49 (22.2)
	1/2" (12.7 mm)	63 (28.6)
8" x 8" x 1/2" (203.2 x 203.2 x 12.7 mm)	1/4" (6.4 mm)	25 (11.4)
	3/8" (9.5 mm)	37 (16.8)
10" x 10" x 3/8" (254 x 254 x 9.5 mm)	1/4" (6.4 mm)	15 (6.8)
	3/8" (9.5 mm)	23 (10.4)
12" x 12" x 3/8" (304.8 x 304.8 x 9.5 mm)	1/4" (6.4 mm)	13 (5.9)
	3/8" (9.5 mm)	19 (8.6)
3-7/8" x 8" x 3/4" (98.4 x 203.2 x 34.9 mm)	1/4" (6.4 mm)	57 (25.9)
3-7/8" x 8" x 1-3/8" (98.4 x 203.2 x 34.9 mm)	1/4" (6.4 mm)	104 (47.2)
16" x 16" x 1/2" (406.4 x 406.4 x 12.7 mm)	1/4" (6.4 mm)	13 (5.9)
	3/8" (9.5 mm)	19 (8.6)
18" x 18" x 1/2" (457.2 x 457.2 x 12.7 mm)	1/4" (6.4 mm)	12 (5.4)
	3/8" (9.5 mm)	17 (7.7)

This chart is for estimating how much product is needed for a given tile installation. These figures are based on filling the joints to their full depth with no waste.

Colors shown are representative of colors manufactured as accurately as can be produced using the finest methods of printing and reproduction. The final color of the installed joint may vary from the printed color sample.